Artwork Specification Sheet

Foamex Panels & Posters mirdo

www.miragedisplay.co.uk

Artwork requirements

- Please save artwork as CMYK.
- Please set up artwork at 1/4 the final size with 3mm bleed on all outside edges.
- If fonts are used, please outline ALL fonts, where not possible please supply all fonts used.
- Once the artwork is received, we will set up on our template and send you a PDF proof for positioning purposes, please check carefully
- If colour matching is required then please advise.
- We do not print PANTONE, we can print the CMYK equivalent, if you have a preferred CMYK equivalent then please advise.
- Artwork can be supplied by either email, CD/DVD or uploaded to our website www.miragedisplay.co.uk, select Artwork then select Upload Artwork and follow instructions.

LOREAL

CASTING



Quark Xpress

- Set up CMYK at 1/4 final size
- Collect for Output and supply a Low resolution PDF for visual purposes
- If supplying a High Res PDF do not compress and supply with all bleed and crop marks

Illustrator

- Set up CMYK at 1/4 final size
- OUTLINE ALL FONTS
- Turn off all Overprints, supply all Links and flatten Transparency
- If supplying a High Res PDF do not compress and supply with all bleed and crop marks

InDesign

- Set up CMYK at 1/4 final size
- OUTLINE ALL FONTS
- Please save and supply a High Res PDF do not compress and supply with all bleed and crop marks

Photoshop Set up CMYK at 1/4 final size and 320dpi

- - Supply a low resolution PDF for visual purposes
 - If artwork set up in Photoshop, text/logos will not be vectored and will have some pixelation when printed full size,
 - Save out as a JPEG.

Adobe Acrobat

If supplying a PDF as your final artwork, ensure all images are not reduced / compressed, crop marks and bleed are included and visual lines are not included inside the artwork.



mira

rea

glass

custom

Mirage Display Ltd. Unit 11 Marsland Street, Hazel Grove, Stockport SK7 4ER

Ai







